

## DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011

**No. DoP-GB-weber.cem HB40-010713**

1. *Unique identification code of the product-type:*  
weber.cem HB40
2. *Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):*  
weber.cem HB40 (batch/production date/ production site is printed on packaging)
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*  
For uses in buildings and civil engineering works
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):*  
**Saint-Gobain Weber Ltd.**  
Dickens House  
Enterprise Way  
Flitwick  
Beds  
MK45 5BY  
UK  
  
Web: [www.netweber.co.uk](http://www.netweber.co.uk)
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*  
Not applicable
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
AVCP system 2+
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*  
**EN 1504-3:2005**  
**BSI, notified factory control body No. 0086 performed initial inspection of factory and factory production control (FPC) and performs continuous surveillance, assessment and approval of FPC under system 2+ and issued certificates of conformity of factory production control:**  
  
**0086-CPR-595178**
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*  
Not applicable

## 9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Compressive strength	Class R3	EN1504-3:2005
Chloride ion content	≤0.05%	EN1504-3:2005
Adhesive bond	≥1.5 MPa	EN1504-3:2005
Restrained shrinkage	≥1.5 MPa	EN1504-3:2005
Carbonation resistance	Pass	EN1504-3:2005
Elastic modulus	≥15 GPa	EN1504-3:2005
Thermal compatibility	≥1.5 MPa	EN1504-3:2005
Coefficient of thermal expansion	12.0 x 10 <sup>-6</sup> /°C	EN1504-3:2005
Capillary absorption	≤0.5kg·m <sup>-2</sup> h <sup>-0.5</sup>	EN1504-3:2005
Reaction to fire	F	EN1504-3:2005
Dangerous substances	None	EN1504-3:2005

NPD = No performance determined

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:  
Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
Signed for and on behalf of the manufacturer by:

..... James Mead (Marketing Manager) .....  
(name and function)

Flitnick (1/7/13) .....  
(place and date of issue) (signature)

Attachments to DoP according to CPR Article 6 (5) and the REACH regulation (EC) No 1907/2006, Article 31 or Article 33

- (31) Safety data sheet: MSDS (weber.cem HB40)
- (33) Information on substances of very high concern: Not applicable