DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011

No. DoP-GB-weber.cem lightweight-010713

1. *Unique identification code of the product-type:*
   weber.cem lightweight

2. *Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):*
   weber.cem lightweight (batch/production date/ production site is printed on packaging)

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
   For uses in buildings and civil engineering works

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):*
   Saint-Gobain Weber Ltd.
   Dickens House
   Enterprise Way
   Flitwick
   Beds
   MK45 5BY
   UK

   Web: www.netweber.co.uk

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
   Not applicable

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
   AVCP system 2+

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*
   EN 1504-3:2005
   BSI, notified factory control body No. 0086 performed initial inspection of factory and factory production control (FPC) and performs continuous surveillance, assessment and approval of FPC under system 2+ and issued certificates of conformity of factory production control:

   0086-CPR-595178

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*
   Not applicable

9. *Declared performance*

Essential characteristics	Performance	Harmonized technical specification
Compressive strength	Class R2	EN1504-3:2005
Chloride ion content	≤0.05%	EN1504-3:2005
Adhesive bond	≥0.8 MPa (≥0.5 MPa for cohesive failure in mortar)	EN1504-3:2005
Restrained shrinkage	≥0.8 MPa	EN1504-3:2005
Carbonation resistance	NPD	EN1504-3:2005
Thermal compatibility	≥0.8 MPa	EN1504-3:2005
Coefficient of thermal expansion	$9.5 \times 10^{-6/o}C$	EN1504-3:2005
Capillary absorption	$\leq 0.5 kg \cdot m^{-2} h^{-0.5}$	EN1504-3:2005
Reaction to fire	F	EN1504-3:2005
Dangerous substances	None	EN1504-3:2005

NPD = No performance determined

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:
Not applicable

10. *The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.*
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:

James Mead (Marketing)
(name and function)

Flitwick (1/7/13)
(place and date of issue)

(signature)

Attachments to DoP according to CPR Article 6 (5) and the REACH regulation (EC) No 1907/2006, Article 31 or Article 33

1. *(31) Safety data sheet:* MSDS *(weber.cem lightweight)*
2. *(33) Information on substances of very high concern:* Not applicable