

## DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011

### No. DoP-GB-weber.tec aquapel crème-220716

1. *Unique identification code of the product-type:*  
**weber.tec aquapel crème**
2. *Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):*  
**weber.tec aquapel crème (batch/production date/ production site is printed on packaging)**
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*  
**Surface protection products – Hydrophobic Impregnation  
Protection against ingress (1.1)  
Moisture control (2.1)**
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):*  
**Saint-Gobain Weber**  
*Dickens House  
Enterprise Way  
Flitwick  
Beds  
MK45 5BY  
UK*  
  
Web: [www.netweber.co.uk](http://www.netweber.co.uk)
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*  
**Not applicable**
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
**AVCP system 2+**
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*  
**EN 1504-2:2004**  
**Qualitätsgemeinschaft Deutsche Bauchemie <sup>E.V.</sup>, notified factory control body No. 0921 performed initial inspection of factory and factory production control (FPC) and performs continuous surveillance, assessment and approval of FPC under system 2+ and issued certificates of conformity of factory production control:**  
  
**0921-CPR-2015**
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*  
**Not applicable**

## 9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Depth of penetration	class II: $\geq 10$ mm	EN1504-2:2004
Water adsorption and resistance to alkali	absorption ratio < 7,5 % compared with the untreated specimen < 10 % after immersion in alkali solution	EN1504-2:2004
Drying rate for hydrophobic impregnation	class I: > 30 %	EN1504-2:2004
Loss of mass after freeze-thaw salt stress	Fulfilled (weight loss at least 20 cycles later than untreated sample)	EN1504-2:2004
Release of dangerous substances	NPD	

NPD = No performance determined

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:  
Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
Signed for and on behalf of the manufacturer by:

..... JAMES MEAD (TECHNICAL DIRECTOR) .....

(name and function)

..... FLITWICK 03/08/16 .....

(place and date of issue) (signature)

Attachments to DoP according to CPR Article 6 (5) and the REACH regulation (EC) No 1907/2006, Article 31 or Article 33

- (31) Safety data sheet: MSDS (weber.tec aquapel crème )
- (33) Information on substances of very high concern: Not applicable