

## **DECLARATION OF PERFORMANCE**

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom

No: DoP-UKCA- webertec Aquapel Crème-101122

1. Unique identification code of the product-type:

webertec Aquapel Crème

2. Intended use/es:

Surface protection products – Hydrophobic Impregnation Protection against ingress (1.1) Moisture control (2.1)

3. Manufacturer:

Saint-Gobain Construction Products UK Limited trading as Saint-Gobain Weber Dickens House Enterprise Way Flitwick Beds MK45 5BY UK

Web: www.uk.weber

4. System/s of AVCP:

AVCP system 2+

5. Designated standard:

EN 1504-2:2004

6. Approved body/ies:

Not applicable

7. Declared performance/s:





Essential characteristics	Performance	Standard
Depth of penetration	class I: < 10 mm	EN 13579+EN 14630 (EN 1504-2:2004)
Water adsorption and resistance to alkali	absorption ratio < 7,5 % compared with the untreated specimen < 10 % after immersion in alkali solution	EN 13580:2003 (EN 1504-2:2004)
Drying rate for hydrophobic impregnation	class I: > 30 %	EN 13579:2003 (EN 1504-2:2004)
Loss of mass after freeze- thaw salt stress	Fulfilled (weight loss at least 20 cycles later than untreated sample)	EN 13581:2003 (EN 1504-2:2004)
Reaction to fire	Class E	EN 13501-1:2018 (EN 1504-2:2005)
Dangerous substances	Refer to current safety data sheets (SDS)	EN 1504-2:2005, 5.4

## NPD = No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[name]	Lee Lambley		
At [place]	fitwick.	On [date of issue]	10/11/22
[signature]	/ lmll	ly:	

