

Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weberfloor DPM hardener

Safety data sheet no.: 44P4026A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

Enterprise Way

Flitwick

Bedfordshire MK45 5BY

Tel.: 01525 718877

webersds@saint-gobain.com

1.4 Emergency telephone number:

UK: NHS 111 (Members of the public)

UK NPIS 24-hour telephone helpline: +44 (0)344 892 0111 (Healthcare professionals only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger



Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

Trade name weberfloor DPM hardener

(Contd. of page 1)

Hazard-determining components of labelling:

m-phenylenebis(methylamine)

decarboxylating cashew nut shell liquid

Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH071 Corrosive to the respiratory tract.

EUH208 Contains decarboxylating cashew nut shell liquid. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:			
CAS: 1477-55-0			
EINECS: 216-032-5	Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412		
Reg.nr.: 01-2119480150-50-xxxx	4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412		
CAS: 8007-24-7	decarboxylating cashew nut shell liquid	25-50%	
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

(Contd. on page 3)



Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

Trade name weberfloor DPM hardener

(Contd. of page 2)

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

Remove contaminated gloves, clothing, footwear or other items and wash thoroughly before re-use.

Cover wound with a sterile dressing.

Seek immediate medical advice.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

Seek immediate medical advice.

After swallowing Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents Water.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Ammonia (NH3)

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Mouth respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

6.2 Environmental precautions:

The product must not get into watercourses

or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Suppress gases/fumes/haze with water spray.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to point 13.

Ensure adequate ventilation.

(Contd. on page 4)



Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

Trade name weberfloor DPM hardener

(Contd. of page 3)

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Use only in well ventilated areas.

Information about fire - and explosion protection: Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities: No further data; see item 7. Ingredients with limit values that require monitoring at the workplace:

DNELs		
CAS: 147	7-55-0 m-phenylenebis(methylamine)
Dermal	Derived No Effect Level	0.33 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	1.2 mg/m³ (worker systemic long term value)
		0.2 mg/m³ (worker local long term value)
PNECs		
CAS: 147	7-55-0 m-phenylenebis(methylamine)
Predicted	No-Effect Concentration	0.0094 mg/l (sea water rating factor)

0.094 mg/l (fresh water rating factor)

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)



Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

Trade name weberfloor DPM hardener

(Contd. of page 4)

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: Protective gloves.

Material of gloves
Butyl rubber, BR
Nitrile rubber, NBR
PVC gloves
PVA gloves

Eye protection: Tightly sealed goggles

Face protection

Vapour density

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties			
9.1 Information on basic physical and che	mical properties		
General Information			
Appearance:			
Form:	Liquid		
Colour:	Dark brown		
Odour: Odour threshold:	Ammonia-like Not determined.		
pH-value:	Alkaline		
Change in condition			
Melting point/freezing point:	Undetermined. >200 °C (DIN)		
Initial boiling point and boiling range:			
Flash point:	94 °C		
Flammability (solid, gas):	Not applicable.		
Ignition temperature:	395-405 °C (DIN 51794)		
Decomposition temperature:	Not determined.		
Auto-ignition temperature:	Product is not self-igniting.		
Explosive properties:	Product does not present an explosion hazard.		
Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
Oxidising properties	Not determined.		
Vapour pressure at 25 °C:	0 hPa (DIN 51640)		
Density:	Not determined		
Bulk density:	Not applicable.		
Relative density	Not determined.		

Not determined.

(Contd. on page 6)



Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

Trade name weberfloor DPM hardener

	(Contd. of pag	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix	
Segregation coefficient (n-octanol/v	water) log	
Pow:	Not determined.	
Viscosity:		
dynamic:	Not determined.	
kinematic:	Not determined.	
Solvent separation test:	Not determined	
Solvent content:		
EU-VOC (%)	0.0000 %	
EU-VOC (g/L)	0.0000 g/l	
Solids content:	0.0 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Ammonia

Aldehyde

Hydrocarbons

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

LD/LC50 values relevant for classification:

Compo	nents	1	Туре	1	Value	1	Species
CAS: 14	177-55	-0 m-pheny	lenebis(m	ethy	lamine)		
Oral	LD50	930 mg/kg	(Rat)				
Dermal	LD50	>3,100 mg	/kg (Rabbit))			

Primary irritant effect:

Skin corrosion/irritation

Causes severe skin burns and eye damage.

(Contd. on page 7)



Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

Trade name weberfloor DPM hardener

(Contd. of page 6)

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects (H412).

Harmful to aquatic life with long lasting effects.

Type of test / Effective concentration / Method / Assessment

CAS: 1477-55-0 m-phenylenebis(methylamine)

LC50/96h 87.6 mg/l (Oryzias latipes (Japanese medaka))

EC50/48h | 15.2 mg/l (Daphnia magna)

EC50/72h 20.3 mg/l (Scenedesmus subspicatus (Algae))

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

Ecotoxical effects:

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Harmful to fish

Additional ecological information:

General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

GE



Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

Trade name weberfloor DPM hardener

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name ADR IMDG, IATA	2735 AMINES, LIQUID, CORROSIVE, N.O.S. AMINES, LIQUID, CORROSIVE, N.O.S.
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups	Warning: Corrosive substances. C7 F-A,S-B (SGG18) Alkalis
14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	f Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.



Printing date 16.12.2022 Version number 4 Revision: 15.12.2022

Trade name weberfloor DPM hardener

(Contd. of page 8)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (UK REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (GB CLP)

"Control of Substances Hazardous to Health" UK Regulations 2002 (as amended)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: EHS

Contact:

webersds

01525718877

webersds@saint-gobain.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

(Contd. on page 10)





Printing date 16.12.2022 Revision: 15.12.2022 Version number 4

Trade name weberfloor DPM hardener

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
* Data compared to the previous version altered.

According to Annex II of the UK REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.