

Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name weberwall brick pointing mortar

Safety data sheet no.: 44P45989

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

Enterprise Way

Flitwick

Bedfordshire MK45 5BY

Tel.: 01525 718877

webersds@saint-gobain.com

1.4 Emergency telephone number:

UK: NHS 111 (Members of the public)

UK NPIS 24-hour telephone helpline: +44 (0)344 892 0111 (Healthcare professionals only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger



Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

Trade name weberwall brick pointing mortar

(Contd. of page 1)

Hazard-determining components of labelling:

cement portland, grey calcium dihydroxide

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

Precautionary statements

P261 Avoid breathing dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor. P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture consisting of the following components.

	9 1	
Dangerous components:		
CAS: 65997-15-1	cement portland, grey	10-20%
EINECS: 266-043-4	 Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 % 	
CAS: 1305-62-0 EINECS: 215-137-3	calcium dihydroxide © Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3,	≥5-<10%
Reg.nr.: 01-2119475151-45-xxxx CAS: 1332-58-7	Kaolin	2-5%
EC number: 310-194-1	substance with a Community workplace exposure limit	

Additional information

For the wording of the listed hazard phrases refer to section 16.

The mixture is 'low chromate' according to EC regulations within the product shelf-life, so that the identification with H317 + EUH203 is not applicable when the packaging was not opened in the meantime.

- GE



Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

Trade name weberwall brick pointing mortar

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact Generally the product does not irritate the skin.

After eye contact

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C).

After swallowing If symptoms persist consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray

or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** No special measures required.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: None.

(Contd. on page 4)



Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

Trade name weberwall brick pointing mortar

(Contd. of page 3)

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities: No further data; see item 7. Ingredients with limit values that require monitoring at the workplace:

		<u> </u>			
DNELs	DNELs				
CAS: 130	CAS: 1305-62-0 calcium dihydroxide				
Inhalative	Derived No Effect Level	4 mg/m³ (worker local short term value)			
		1 mg/m³ (worker local long term value)			
		1 mg/m³ (consumer local long term value)			
		4 mg/m³ (consumer local short term value)			
PNECs	PNECs				
CAS: 130	CAS: 1305-62-0 calcium dihydroxide				
Predicted	Predicted No-Effect Concentration 9.32 mg/l (sea water rating factor)				
	0.49 mg/l (fresh water rating factor)				
CAS	CAS No. / Designation of material / % / Type / Value / Unit				
CAS: 659	CAS: 65997-15-1 cement portland, grey				
	WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust				
CAS: 130	CAS: 1305-62-0 calcium dihydroxide				
Lon	WEL Short-term value: 4* mg/m³ Long-term value: 5 1* mg/m³ *resprable fraction				
CAS: 133	2-58-7 Kaolin				
WEL Lon	WEL Long-term value: 2 mg/m³				

Additional Occupational Exposure Limit Values for possible hazards during processing:

Quartz respirable dust (< 5 µm): 0,15 mg/m³

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: Protective gloves. Eye protection: Tightly sealed goggles Body protection: Protective work clothing.



Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

Trade name weberwall brick pointing mortar

(Contd. of page 4)

SECTION 9: Physical and chemical	properties
9.1 Information on basic physical and cher General Information	nical properties
Appearance:	Devedor
Form: Colour:	Powder According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
Flash point:	Not applicable
Flammability (solid, gas):	Product is not flammable.
Ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Oxidising properties	Not determined.
Vapour pressure:	Not applicable.
Density:	Not applicable.
Relative density	Not determined.
Vapour density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with Water:	Insoluble
Segregation coefficient (n-octanol/water) le	og Not determined.
Viscosity:	
dynamic:	Not applicable.
kinematic:	Not applicable.
Solvent content:	0.0.0/
Organic solvents:	0.0 %
Solids content:	100.0 %
9.2 Other information	No further relevant information available.



Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

Trade name weberwall brick pointing mortar

(Contd. of page 5)

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- **10.5** Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compor	nents	1	Туре	1	Value	1	Species	
CAS: 13	17-65·	-3 calcium c	arbonate					
Oral	LD50	>5,000 mg/l	(g (Rat)					
CAS: 65	997-1	5-1 cement	portland,	grey				
Dermal	LD50	>2,000 mg/l	(Rabbit)					
CAS: 13	05-62	-0 calcium d	ihydroxid	е				
Oral	LD50	>2,000 mg/l	(g (Rat)					
Dermal	LD50	>2,500 mg/l	kg (Rabbit)					

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

(Contd. on page 7)



Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

Trade name weberwall brick pointing mortar

(Contd. of page 6)

Type of test	Type of test / Effective concentration / Method / Assessment			
CAS: 1317-6	CAS: 1317-65-3 calcium carbonate			
LC50/96h	.C50/96h >10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))			
EC50/48h	EC50/48h >1,000 mg/l (Daphnia magna)			
EC50/72h	EC50/72h >200 mg/l (Algae)			
CAS: 1305-6	CAS: 1305-62-0 calcium dihydroxide			
LC50/96h 158 mg/l (Daphnia magna)				
	>50.6 mg/l (Fish)			
EC50/48h	EC50/48h 49.1 mg/l (Daphnia magna)			
EC50/72h	EC50/72h 184.57 mg/l (Algae)			
NOEC (14d)	NOEC (14d) 32 mg/l (Daphnia magna)			

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

Ecotoxical effects:

Behaviour in sewage processing plants:

Type of test / Ef	ffective concentration / Method / Assessment
CAS: 1305-62-0	calcium dihydroxide
EC 50 (3h) 300.	4 mg/l (Activated sludge)

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
<u> </u>	VOIU	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR		
Class	- (-)	

(Contd. on page 8)



Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

Trade name weberwall brick pointing mortar

	(Contd. of page
ADN/R Class:	Void
IMDG	
Class	Void
Label	-
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
EMS Number:	-
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (UK REACH) (Candidate List, Annexes XIV and XVII) Regulation (EC) No 1272/2008 (GB CLP)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Department issuing SDS: EHS

Contact:

webersds

01525718877

webersds@saint-gobain.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)

(Contd. of page 8)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.12.2022 Version number 5 Revision: 15.12.2022

Trade name weberwall brick pointing mortar

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

According to Annex II of the UK REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.