

Printing date 07.12.2022 Version number 2 Revision: 18.03.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name weberset pro lite - rapid

Safety data sheet no.: 44P46109

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

**Enterprise Way** 

Flitwick

Bedfordshire MK45 5BY

Tel.: 01525 718877

webersds@saint-gobain.com

### 1.4 Emergency telephone number:

UK: NHS 111 (Members of the public)

UK NPIS 24-hour telephone helpline: +44 (0)344 892 0111 (Healthcare professionals only)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

## 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

#### **Hazard pictograms**





GHS05 GHS07

Signal word Danger



Printing date 07.12.2022 Version number 2 Revision: 18.03.2022

#### Trade name weberset pro lite - rapid

(Contd. of page 1)

#### Hazard-determining components of labelling:

cement portland, grey

## Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

#### **Precautionary statements**

P261 Avoid breathing dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.
P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with non hazardous additions.

Dangerous components:			
	cement portland, grey	10-20%	
	EINECS: 266-043-4 Eye Dam. 1, H318;  Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335		
	Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 %		
	Eye Dam. 1; H318: C ≥ 1 %		

#### Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

### **General information**

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact If skin irritation continues, consult a doctor.

#### After eye contact

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C).

**After swallowing** If symptoms persist consult a doctor.

(Contd. on page 3)



Printing date 07.12.2022 Version number 2 Revision: 18.03.2022

Trade name weberset pro lite - rapid

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

### Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

## **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- **6.2 Environmental precautions:** No special measures required.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

**7.1 Precautions for safe handling** Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

**DNELs** 

CAS: 65997-16-2 Cement, alumina, chemicals

Inhalative Derived No Effect Level 2.5 mg/m³ (worker systemic long term value)

5 mg/m³ (worker systemic short term value)

(Contd. on page 4)



**PNFCs** 

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.12.2022 Version number 2 Revision: 18.03.2022

#### Trade name weberset pro lite - rapid

(Contd. of page 3)

CAS: 65996-69-2 Slags,	ferrous metal,	blast furnace

Predicted No-Effect Concentration | 1,000 mg/kgxdwt (earth rating factor) |
Predicted No-Effect Concentration | 500 mg/l (sea water rating factor)

5,000 mg/l (fresh water rating factor)

## CAS No. / Designation of material / % / Type / Value / Unit

CAS: 65997-15-1 cement portland, grey

WEL Long-term value: 10\* 4\*\* mg/m³ inhalable dust \*\*respirable dust

### 8.2 Exposure controls

Personal protective equipment:

#### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

#### Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter P2.

Protection of hands: Protective gloves.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

## **SECTION 9: Physical and chemical properties**

9.1 Information on t	oasic physical	I and chemica	il properties
General Information	n		

Annonum

Appearance:

Form: Powder Grey

Odour:CharacteristicOdour threshold:Not determined.

pH-value:

Change in condition

Melting point/freezing point:Undetermined.Initial boiling point and boiling range:Undetermined.

Flash point: Not applicable

Flammability (solid, gas): Product is not flammable.

Ignition temperature: Not determined.

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not self-igniting.

**Explosive properties:** Product does not present an explosion hazard.

Not applicable

**Explosion limits:** 

**Lower:** Not determined.

(Contd. on page 5)



Printing date 07.12.2022 Version number 2 Revision: 18.03.2022

#### Trade name weberset pro lite - rapid

	(Cont	d. of pag
Upper:	Not determined.	
Oxidising properties	Not determined.	
Vapour pressure:	Not applicable.	
Density:	Not applicable.	
Relative density	Not determined.	
Vapour density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Insoluble	
Segregation coefficient (n-octanol/w	ater) log	
Pow:	Not determined.	
Viscosity:		
dynamic:	Not applicable.	
kinematic:	Not applicable.	
Solvent content:		
Organic solvents:	0.0 %	
EU-VOC (%)	0.0000 %	
EU-VOC (g/L)	0.0000 g/l	
Solids content:	100 %	
9.2 Other information	No further relevant information available.	

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compo	nents	1	Type	1	Value	1	/ Species
CAS: 6	CAS: 65997-15-1 cement portland, grey						
Dermal	LD50	>2,000 mg/l	(Rabbit)				
Dispers	ion of	a copolyme	r from Vir	ıyl ac	cetate, V	inyl	yl chloride and Ethylene in water
Oral	LD50	>2,000 mg/l	(g (Rat)				

(Contd. on page 6)



Printing date 07.12.2022 Version number 2 Revision: 18.03.2022

#### Trade name weberset pro lite - rapid

		(Contd. of page 5)	
CAS: 6	CAS: 65996-69-2 Slags, ferrous metal, blast furnace		
Oral	LD50	>2,000 mg/kg (Rat)	
Dermal	LD50	>4,000 mg/kg (Rat)	
CAS: 6	CAS: 65997-16-2 Cement, alumina, chemicals		
Oral	LD50	>2,000 mg/kg (Rat)	
Dermal	LD50	>2,000 mg/kg (Rat)	

#### **Primary irritant effect:**

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

Type of test	Type of test / Effective concentration / Method / Assessment			
Dispersion of	Dispersion of a copolymer from Vinyl acetate, Vinyl chloride and Ethylene in water			
LC50/96h	>100 mg/l (Cyprinus Carpio (common carp))			
EC 10	EC 10 >1,000 mg/l (Activated sludge)			
CAS: 65996-	69-2 Slags, ferrous metal, blast furnace			
LC50/96h	>100 mg/l (Leuciscus idus (Orfe))			
LC0/96h	LC0/96h >100 mg/l (Leuciscus idus (Orfe))			
EC50/72h	EC50/72h >90,000 mg/l (Algae)			
NOEC (72h)	NOEC (72h) 50-100 mg/l (Algae)			
NOEC (21d)	NOEC (21d) 1,563 mg/l (Daphnia magna)			
EC 0/48h	EC 0/48h >100 mg /l (Daphnia magna)			
CAS: 65997-	CAS: 65997-16-2 Cement, alumina, chemicals			
LC50/96h	LC50/96h   100 mg/l (Fish)			
EC50/48h	EC50/48h 5.4 mg/l (Daphnia magna)			
EC50/72h	EC50/72h 3.6 mg/l (Algae)			

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)



Printing date 07.12.2022 Version number 2 Revision: 18.03.2022

#### Trade name weberset pro lite - rapid

(Contd. of page 6)

#### **Ecotoxical effects:**

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment

CAS: 65996-69-2 Slags, ferrous metal, blast furnace

EC 50 (3h) >10,000 mg/l (Activated sludge)

CAS: 65997-16-2 Cement, alumina, chemicals

EC 50 (3h) 1,000 mg/l (Activated sludge)

#### Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment PBT:** Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

**12.6 Other adverse effects** No further relevant information available.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Uncleaned packaging:

#### Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent: Thoroughly shake out sacks.

14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR Class ADN/R Class:	- (-) Void	
IMDG Class Label	Void -	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	

(Contd. on page 8)



Printing date 07.12.2022 Version number 2 Revision: 18.03.2022

Trade name weberset pro lite - rapid

	(Contd. of page 7)
EMS Number:	-
14.7 Transport in bulk according to Annex Marpol and the IBC Code	
Transport/Additional information:	Not applicable.  Not dangerous according to the above
TransportiAdditional information.	specifications.
UN "Model Regulation":	Void

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (UK REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (GB CLP)

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

#### **Department issuing SDS: EHS**

#### Contact:

webersds

01525718877

webersds@saint-gobain.com

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 9)





Printing date 07.12.2022 Revision: 18.03.2022 Version number 2

### Trade name weberset pro lite - rapid

(Contd. of page 8)

Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

## \* Data compared to the previous version altered.

According to Annex II of the UK REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.