

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **webertec cable grout resin**

Safety data sheet no.: 44P47197A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

Enterprise Way

Flitwick

Bedfordshire MK45 5BY

Tel: +44(0)1525 718877

webersds@saint-gobain.com

1.4 Emergency telephone number:

- Ireland: National Poisons Information Centre: +353 (1) 809 2166 (Members of the public 8am - 10pm, 7 days a week) ; +353 (1) 809 2566 (Healthcare professionals only 24/7)

- Iceland: Poisons Information Center - Icelandic University Hospital: +354 543 2222

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

styrene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection / face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.


vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32-xxxx	styrene 	25-50%
--	---	--------

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

EUG

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing If symptoms persist consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Mouth respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

6.2 Environmental precautions:

The product must not get into watercourses or into the soil.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Suppress gases/fumes/haze with water spray.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to point 13.

(Contd. on page 4)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 3)

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

DNELs

CAS: 100-42-5 styrene

Oral	Derived No Effect Level	0.0077 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	406 mg/kgxday (worker systemic long term value)
		343 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	85 mg/m ³ (worker systemic long term value)
		1 mg/m ³ (consumer systemic long term value)

(Contd. on page 5)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 4)

Ingredients with biological limit values:
CAS: 100-42-5 styrene

VLB (Spain)	400 mg/g creatinina Muestra: orina Momento de Muestero: Final de la jornada laboral Indicador Biológico: Ácido mandélico más ácido fenilglioxílico
IBE (Italy)	0.2 mg/l Muestra: sangre venosa Momento de Muestero: Final de la jornada laboral Indicador Biológico: Estireno 400 mg/g creatinina Campioni: urine Momento del prelievo: a fine turno Indicatore biologico: acido mandelico + acido fenilgliossilico
IBE (Portugal)	0.2 mg/l Campioni: sangue venoso Momento del prelievo: a fine turno Indicatore biologico: stirene 400 mg/g creatinina Amostra: urina Momento da amostragem: Fim do turno Indicador biológico: Soma do ácido mandélico e ácido fenilglioxílico
BNO (Finland)	0.2 mg/L Amostra: sangue venoso Momento da amostragem: Fim do turno Indicador biológico: Estireno 1.2 mmol/l Altiste: virtsan Näytteenottoajankohta: Työpäivän jälkeinen aamu Parametri: MAPGA

CAS No. / Designation of material / % / Type / Value / Unit
CAS: 100-42-5 styrene

MAK (Germany)	Long-term value: 86 mg/m ³ , 20 ppm vgl.Abschn.XII
TWA (Italy)	Short-term value: 170 mg/m ³ , 40 ppm Long-term value: 85 mg/m ³ , 20 ppm A4, IBE
VLE (Portugal)	Short-term value: 40 ppm Long-term value: 20 ppm A4;IBE;SCN; irrit. do TRS; neuropatia periférica
HTP (Finland)	Short-term value: 430 mg/m ³ , 100 ppm Long-term value: 86 mg/m ³ , 20 ppm melu

8.2 Exposure controls
Appropriate engineering controls No further data; see item 7.

(Contd. on page 6)

-EUG-

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 5)

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection Protective gloves.

Eye/face protection Safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

Amber coloured

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

145 °C (DIN, CAS: 100-42-5 styrene)

Flammability

Not applicable.

Lower and upper explosion limit

Lower:

1.2 Vol % (DIN 51649, CAS: 100-42-5 styrene)

Upper:

8.9 Vol % (DIN 51649, CAS: 100-42-5 styrene)

Flash point:

31 °C (DIN ISO 2592, CAS: 100-42-5 styrene)

Ignition temperature:

490 °C (DIN 51794, CAS: 100-42-5 styrene)

Decomposition temperature:

Not determined.

pH

Not applicable.

Not determined.

Viscosity:

Kinematic viscosity at 20 °C

200 mm²/s (DIN ISO 2431)

Not determined.

dynamic:

Not determined.

Solubility

Water:

Fully miscible

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C:

6.7 hPa (DIN 51640)

Density and/or relative density

Density:

Not determined

Relative density

Not determined.

Bulk density:

Not applicable.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 6)

Vapour density	Not determined.
-----------------------	-----------------

9.2 Other information

Appearance:

Form:	Liquid
--------------	--------

Important information on protection of health and environment, and on safety.

Auto-ignition temperature:	Product is not self-igniting.
-----------------------------------	-------------------------------

Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
------------------------------	---

Minimum ignition energy	
--------------------------------	--

Solvent separation test:	Not applicable.
---------------------------------	-----------------

Solvent content:	
-------------------------	--

Organic solvents:	34.0 %
--------------------------	--------

EU-VOC (g/L)	
---------------------	--

Solids content:	66.0 %
------------------------	--------

Change in condition	
----------------------------	--

Softening point/range	
------------------------------	--

Oxidising properties	Not determined.
-----------------------------	-----------------

Evaporation rate	Not determined.
-------------------------	-----------------

Information with regard to physical hazard classes

Explosives	Void
-------------------	------

	Void
--	------

Flammable gases	Void
------------------------	------

	Void
--	------

Aerosols	Void
-----------------	------

	Void
--	------

Oxidising gases	Void
------------------------	------

	Void
--	------

Gases under pressure	Void
-----------------------------	------

	Void
--	------

Flammable liquids	Flammable liquid and vapour.
--------------------------	------------------------------

	Void
--	------

Flammable solids	Void
-------------------------	------

	Void
--	------

Self-reactive substances and mixtures	Void
--	------

	Void
--	------

Pyrophoric liquids	Void
---------------------------	------

	Void
--	------

Pyrophoric solids	Void
--------------------------	------

	Void
--	------

Self-heating substances and mixtures	Void
---	------

	Void
--	------

Substances and mixtures, which emit flammable gases in contact with water	Void
--	------

	Void
--	------

Oxidising liquids	Void
--------------------------	------

	Void
--	------

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 7)

Oxidising solids	Void
	Void
Organic peroxides	Void
	Void
Corrosive to metals	Void
	Void
Desensitised explosives	Void
	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	/	Type	/	Value	/	Species
CAS: 100-42-5 styrene						
Oral	LD50			>6,000 mg/kg		(Rat)
Dermal	LD50			>2,000 mg/kg		(Rat)
Inhalative	LC50/4 h			24 mg/l		(Rat)

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Suspected of damaging the unborn child.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

EUG

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects (H412).

Harmful to aquatic life with long lasting effects.

Type of test / Effective concentration / Method / Assessment

CAS: 100-42-5 styrene

EC50/48h 4.7 mg/l (Daphnia magna)

EC50/96h 3.32 mg/l (Fish)

EC50/72h 4.9 mg/l (Algae)

NOEC (21d) 1.01 mg/l (Daphnia magna)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

European waste catalogue

HP3 Flammable

HP4 Irritant - skin irritation and eye damage

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP10 Toxic for reproduction

HP14 Ecotoxic

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

EUG

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 9)

SECTION 14: Transport information

14.1 UN number or ID number
ADR, IMDG, IATA

UN1866

14.2 UN proper shipping name
ADR
IMDG, IATA

1866 RESIN SOLUTION
RESIN SOLUTION

14.3 Transport hazard class(es)
ADR



Class
Label

3 (F1) Flammable liquids.
3

IMDG, IATA



Class
Label

3 Flammable liquids.
3

14.4 Packing group
ADR, IATA

III

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user
Hazard identification number (Kemler code): 30
EMS Number:

Warning: Flammable liquids.
F-E, S-E

14.7 Maritime transport in bulk according to
IMO instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)
Excepted quantities (EQ)

5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

Transport category
Tunnel restriction code

3
D/E

IMDG

Remarks:

> 5l: 3 III

UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

EUG

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 10)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 12)

EUG

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 2 (replaces version 1)

Revision: 13.08.2021

Trade name webertec cable grout resin

(Contd. of page 11)

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/eye irritation Reproductive toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: EHS
Contact:

webersds

+44(0)1525718877

webersds@saint-gobain.com

Version number of previous version: 1
Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EUG