

DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom

No: DoP-UKCA-weberset SPF-080323

1. Unique identification code of the product-type:

weberset SPF

2. Intended use/es:

All internal and external tiling

3. Manufacturer:

Saint-Gobain Construction Products UK Limited trading as Saint-Gobain Weber
Dickens House
Enterprise Way
Flitwick
Beds
MK45 5BY
UK

Web: www.uk.weber

4. System/s of AVCP:

System 3 (system 4 for reaction to fire)

5. Designated standard:

EN 12004:2007+A1:2012

6. Approved body/ies:

Lucideon (1289)

7. Declared performance/s:

C2S1

Essential characteristics	Performance	Standard
Reaction to fire	E CWFT	EN 12004:2007+A1:2012, 4.4.3
Release of dangerous substances	See SDS	EN 12004:2007+A1:2012
Bond strength, as:		
Early tensile adhesion strength	$\geq 0.5 \text{ N/mm}^2$	EN 1348:2007 (EN 12004:2007+A1:2012)
Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$	EN 1348:2007 (EN 12004:2007+A1:2012)
Durability for:		
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$	EN 1348:2007 (EN 12004:2007+A1:2012)
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$	EN 1348:2007 (EN 12004:2007+A1:2012)
Tensile adhesion strength after freeze/thaw cycles	$\geq 1.0 \text{ N/mm}^2$	EN 1348:2007 (EN 12004:2007+A1:2012)

NPD = No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[name] LEE LAMBLY

At [place] Elitazick On [date of issue] 08/03/23

[signature] 