

## **DECLARATION OF PERFORMANCE**

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom

No: DoP-UKCA-weberset rapid plus-080323

1. Unique identification code of the product-type:

weberset rapid plus

2. Intended use/es:

All internal and external tiling

3. Manufacturer:

Saint-Gobain Construction Products UK Limited trading as Saint-Gobain Weber Dickens House **Enterprise Way Flitwick** Beds **MK45 5BY** UK

Web: www.uk.weber

4. System/s of AVCP:

System 3 (system 4 for reaction to fire)

5. Designated standard:

EN 12004:2007+A1:2012

6. Approved body/ies:

Lucideon (1289)

7. Declared performance/s:

C2FT





Essential characteristics	Performance	Standard
Reaction to fire	E CWFT	EN 12004:2007+A1:2012, 4.4.3
Release of dangerous substances	See SDS	EN 12004:2007+A1:2012
Bond strength, as:		
Early tensile adhesion strength	≥0.5N/mm²	EN 1348:2007 (EN 12004:2007+A1:2012)
Initial tensile adhesion strength	≥1.0N/mm²	EN 1348:2007 (EN 12004:2007+A1:2012)
Durability for:		
Tensile adhesion strength after heat ageing	≥1.0N/mm²	EN 1348:2007 (EN 12004:2007+A1:2012)
Tensile adhesion strength after water immersion	≥1.0N/mm²	EN 1348:2007 (EN 12004:2007+A1:2012)
Tensile adhesion strength after freeze/thaw cycles	≥1.0N/mm²	EN 1348:2007 (EN 12004:2007+A1:2012)

NPD = No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

On [date of issue]

Signed for and on behalf of the manufacturer by:

LEE LAMBIOT [name]

At [place]

[signature]