

# **DECLARATION OF PERFORMANCE**

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014

No: DoP-CE-weberend PTC-ddmmyy

1.	Unique identification	code	of the	product-type:
	weberend PTC			

#### 2. Intended use/es:

Coloured rendering mortar (CR) for external use

#### 3. Manufacturer:

Saint-Gobain Construction Products UK Limited trading as Saint-Gobain Weber Dickens House Enterprise Way Flitwick Beds MK45 5BY UK

Web: www.uk.weber

## 4. System/s of AVCP:

System 4

### 5. Harmonised standard:

EN 998-1:2016

#### 6. Notified body/ies:

Not applicable

## 7. Declared performance/s:

EN 998-1





Essential characteristics	Performance	Standard			
Capillary water absorption	Wc2 class $C \leq 0.2 \text{ kg/(m}^2.\text{min}^{0.5})$	BS EN 1015-18:2002 (EN 998-1:2016)			
Water vapour permeability	µ ≤30	BS EN 1015-19:1999 (EN 998-1:2016)			
Thermal conductivity	0.82 W/(m.K)	EN 1745:2012, Table A.12 (EN 998-1:2016)			
Reaction to fire	Class A2 - s1,d0	BS EN 13501-1 :2018 (BS EN 998-1:2016, 5.3.3)			
Durability:	EN 998-1:2016, 5.3.2				
Adhesion after weathering cycles	≥0.2 MPa Failure mode A & B	BS EN 1015-21:2002 (EN 998-1:2016)			
Water permeability after weathering cycles	≤1 ml/cm2 after 48 hours				
Dangerous substances See SDS		EN 998-1:2016, 5.3.4			

NPD = No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[name]

LEE LAMBUET LITWICK On [date of issue]

At [place]

06/09/23.

[signature]