

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: weber.tec EP structural adhesive standard grade resin

Safety data sheet no.: 44P46098

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

Enterprise Way

Flitwick

Bedfordshire MK45 5BY

Tel.: 01525 718877

webersds@saint-gobain.com

1.4 Emergency telephone number:

UK: NHS 111 (Members of the public)

UK NPIS 24-hour telephone helpline: +44 (0)344 892 0111 (Healthcare professionals only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07 GHS09

Signal word Warning

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 1)

Hazard-determining components of labelling:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane

1,6-Hexanediol, reaction products with epichlorohydrin

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures
Description: Mixture of substances listed below with non hazardous additions.

Dangerous components:

CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-xxxx	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-20%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-xxxx	Reaction product: bisphenol-A-(epichlorohydrin), epoxy resin (number average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	10-20%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-xxxx	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	2-5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 2)		
CAS: 16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane	2-5%
EINECS: 240-260-4	⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
Reg.nr.: 2119463471-41-xxxx		

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

 Carbon monoxide (CO)

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 3)

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Prevent any seepage into the ground.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:

DNELs

CAS: 9003-36-5 Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	Derived No Effect Level	6.25 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	104.15 mg/kgxday (worker systemic long term value)
		62.5 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	23.39 mg/m ³ (worker systemic long term value)
		8.7 mg/m ³ (consumer systemic long term value)

CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin),epoxy resin (number average molecular weight ≤ 700)

Oral	Derived No Effect Level	0.75 mg/kgxday (consumer systemic long term value)
		0.75 mg/kgxday (consumer systemic short term value)
Dermal	Derived No Effect Level	8.33 mg/kgxday (worker systemic long term value)
		8.33 mg/kgxday (worker systemic short term value)
		3.571 mg/kgxday (consumer systemic long term value)
		3.571 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	12.3 mg/m ³ (worker systemic long term value)
		12.3 mg/m ³ (worker systemic short term value)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 4)

CAS: 100-51-6 Benzyl alcohol

Oral	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	8 mg/kgxday (worker systemic long term value)
		4 mg/kgxday (consumer systemic long term value)
Inhalative	Derived No Effect Level	22 mg/m ³ (worker systemic long term value)
		5.4 mg/m ³ (consumer systemic long term value)

8.2 Exposure controls
Personal protective equipment:
General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.

Filter A2/P2.

Protection of hands: Protective gloves.

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

Penetration time of glove material

Thickness ≥ 0.4mm.

Recommend a maximum wearing time which corresponds to 50% of penetration time.

Eye protection: Goggles recommended during refilling

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:

Form:	Fluid Paste.
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value:	Not applicable.
------------------	-----------------

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

Flash point:	Not applicable
---------------------	----------------

Flammability (solid, gas):	Not applicable.
-----------------------------------	-----------------

Auto-ignition temperature:	184 °C (DIN 51794)
-----------------------------------	--------------------

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 5)

Decomposition temperature:	Not determined.
Ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	1.3 Vol % (DIN 51649)
Upper:	13.0 Vol % (DIN 51649)
Oxidising properties	Not determined.
Vapour pressure at 20 °C:	0.1 hPa (DIN 51640)
Density:	Not determined
Bulk density:	Not applicable.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix
Segregation coefficient (n-octanol/water) log Pow:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent separation test:	Not determined
Solvent content:	
Organic solvents:	2.0 %
Solids content:	66.3 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

May produce violent reactions with bases and numerous organic substances including alcohols and amines

Exothermic polymerisation.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

-GB-

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 9003-36-5 Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			
Oral	LD50	>5,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)
CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)			
Oral	LD50	>5,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)
CAS: 100-51-6 Benzyl alcohol			
Oral	LD50	1,230 mg/kg	(Rat)
Dermal	LD50	2,000 mg/kg	(Rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)	
		>4,178 mg/l	(Rat)
CAS: 16096-31-4 1,6-bis(2,3-epoxypropoxy)hexane			
Oral	LD50	2,190 mg/kg	(Rat)
Dermal	LD50	<4,900 mg/kg	(Rabbit)
Inhalative	LC50/4 h	>100 mg/l	(Mouse)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 7)

Type of test / Effective concentration / Method / Assessment
CAS: 9003-36-5 Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

LC50/48h	2.55 mg/l (Daphnia magna)
LC50/96h	2.54 mg/l (Leuciscus idus (Orfe))
EC50/48h	2.55 mg/l (Daphnia magna)
EC50/96h	2.54 mg/l (Leuciscus idus (Orfe))

CAS: 25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)

LC50/96h	2 mg/l (Leuciscus idus (Orfe)) 1.3 mg/l (Fish)
EC50/24h	4.6 mg/l (Daphnia magna)
EC50/48h	1.8 mg/l (Daphnia magna)
EC50/96h	220 mg/l (Selenastrum capricornutum (Green algae))
NOEC (21d)	0.3 mg/l (Daphnia magna)

CAS: 100-51-6 Benzyl alcohol

LC50/48h	360 mg/l (Daphnia magna) 645 mg/l (Leuciscus idus (Orfe))
LC50/96h	10 mg/l (Lepomis macrochirus (Sunfish)) 460 mg/l (Pimephales promelas (Minnow))
EC50/24h	400 mg/l (Daphnia magna)
EC50/96h	400 mg/l (Daphnia magna) 640 mg/l (Scenedesmus subspicatus (Algae))
EC50/72h	770 mg/l (Algae)
EC 10	400 mg/l (Pseudomonas putida (Bacteria))

CAS: 16096-31-4 1,6-bis(2,3-epoxypropoxy)hexane

LC50/96h	30 mg/l (Leuciscus idus (Orfe))
EC50/48h	47 mg/l (Daphnia magna)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential
CAS: 100-51-6 Benzyl alcohol

EBAB	1.1 log Pow (Bioaccumulation)
------	-------------------------------

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:
Behaviour in sewage processing plants:
Type of test / Effective concentration / Method / Assessment
CAS: 100-51-6 Benzyl alcohol

EC 50 (3h)	79 mg/l (Scenedesmus quadricauda (Algae))
------------	---

Additional ecological information:
General notes: Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment
PBT: Does not contain PBT substances.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 8)

vPvB: Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Uncleaned packaging:
Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN3082

14.2 UN proper shipping name
ADR
IMDG
IATA

3082 ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S.
ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S., MARINE POLLUTANT
ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S.

14.3 Transport hazard class(es)

ADR, IMDG, IATA

Class
Label

9 Miscellaneous dangerous substances and articles.
9

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:

Marine pollutant:

Yes
Symbol (fish and tree)

Special marking (ADR):

Symbol (fish and tree)

Special marking (IATA):

Symbol (fish and tree)

14.6 Special precautions for user

Warning: Miscellaneous dangerous substances and articles.

EMS Number:

F-A,S-F

Stowage Category

A

14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code

Not applicable.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 9)

Transport/Additional information:

ADR

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Tunnel restriction code

E

UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S., 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"Control of Substances Hazardous to Health" UK Regulations 2002 (as amended)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: EHS

Contact:

webersds

01525718877

webersds@saint-gobain.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.09.2023

Version number 5

Revision: 19.09.2023

Trade name: weber.tec EP structural adhesive standard grade resin

(Contd. of page 10)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

According to Annex II of the UK REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

—GB—