

## DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom

No: DoP-UKCA-weberend TTC-150323

**1. Unique identification code of the product-type:**

weberend TTC

**2. Intended use/es:**

Coloured rendering mortar (CR) for external use

**3. Manufacturer:**

Saint-Gobain Construction Products UK Limited trading as Saint-Gobain Weber  
Dickens House  
Enterprise Way  
Flitwick  
Beds  
MK45 5BY  
UK

Web: [www.uk.weber](http://www.uk.weber)

**4. System/s of AVCP:**

System 4

**5. Harmonised standard:**

EN 998-1:2016

**6. Notified body/ies:**

Not applicable

**7. Declared performance/s:**

EN 998-1

Essential characteristics	Performance	Standard
Capillary water absorption	Wc2 class $C \leq 0.2 \text{ kg}/(\text{m}^2 \cdot \text{min}^{0.5})$	BS EN 1015-18:2002 (EN 998-1:2016)
Water vapour permeability	$\mu \leq 35$	BS EN 1015-19:1999 (EN 998-1:2016)
Thermal conductivity	0.82 W/(m.K)	EN 1745:2012, Table A.12 (EN 998-1:2016)
Reaction to fire	Class A1 (<1% organic content)	BS EN 998-1:2016, 5.3.3
Adhesion	$\geq 0.2 \text{ MPa}$ Failure mode A & B	BS EN 1015-12:2016 (EN 998-1:2016)
Durability:		EN 998-1:2016, 5.3.2
Adhesion after weathering cycles	$\geq 0.2 \text{ MPa}$ Failure mode A & B	BS EN 1015-21:2002 (EN 998-1:2016)
Water permeability after weathering cycles	$\leq 1 \text{ ml}/\text{cm}^2$ after 48 hours	
Dangerous substances	See SDS	EN 998-1:2016, 5.3.4

NPD = No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[name]

LEE LAMBLEY

At [place]

FLITWICK

On [date of issue]

16/03/23

[signature]

*[Handwritten signature]*