

*High-performance, silane-based
water repellent*

webertec aquapel crème



About this product

webertec aquapel crème is an aqueous, water-based creamy, silane-based water repellent. **webertec aquapel crème** is designed to penetrate deeply into the concrete so as to afford optimum protection against absorption of water and pollutants as well as freeze/thaw cycles.

Technical data

Complies with BS EN1504-2. DOP available on request

Uses

For treatment of:

- Porous concrete
- Buildings and structures in exposed locations
- Protection of bridges and other structures from salt spray
- Masonry substrates

Features and benefits

- ▲ One-coat application
- ▲ Easy to apply by brush, roller or non-atomising spray
- ▲ Minimal effect to surface appearance
- ▲ Protects against ingress of water-borne ions (chlorides and sulphates)
- ▲ Improves freeze/thaw resistance of treated surfaces
- ▲ Reduces susceptibility to corrosion of reinforcement
- ▲ Allows treated surface to breathe
- ▲ Enhanced durability
- ▲ Provides good adhesion for paints

Constraints

Not to be used in buildings that are subject to fire regulations.

Effectiveness of the product will be impacted by the porosity of the substrate. Substrates with low porosity will receive less benefit from an application of **webertec aquapel crème**. All testing of **webertec aquapel crème** has been completed on substrates in accordance with EN 1504-2.

webertec aquapel crème

Preparation

Surfaces must be sound, clean, dry, free from oil or other contamination before the treatment is applied. New concrete should be at least 28 days old before application and all traces of laitance, shutter release or curing membrane should be removed and the surface allowed to dry out thoroughly.

Old weathered surfaces should be wire brushed to remove lichen, algae, dust and any loose or flaky material. For large areas, water jetting or grit blasting may be more effective. After applying water, allow at least 3 days of dry, warm weather (minimum 15°C) and make good all cracks and spalled surfaces before applying the material.

Apply in dry weather only.

Coverage

Approximately 2.25 m² per litre.

Storage and shelf life

Store in a cool, dry place above 5°C.

Shelf life of unopened container in correct storage conditions is at least 12 months.

Health and safety

For further information, please request the Material Safety Data Sheet for this product.

Application

webertec aquapel crème is best applied to the substrate by lambskin rollers or spatulas. For large areas airless spray machines may be used. Once applied the material will form a thick layer on the surface which will be absorbed into the surface.

One coat is normally sufficient. In the event of unexpected rain, cover surfaces already treated and halt any further application until the surface to be treated is dry.

Avoid direct contact with asphalt based substrates and coatings.

Cleaning

Clean all brushes and tools with water immediately after use.

Packaging

webertec aquapel crème is supplied in 10 litre buckets.

Technical services

Weber's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical helpline

Tel: 01525 718877

e-mail technical@netweber.co.uk

Sales enquiries

Weber products are distributed throughout the UK through selected stockists and distributors. Please contact the relevant Customer Services Team below for all product orders and enquiries.

UK and Ireland

Tel: 01525 718877

e-mail customerservice@netweber.co.uk

Saint-Gobain Weber

Dickens House, Enterprise Way, Maulden Road, Flitwick, Bedford MK45 5BY, UK
Tel: 01525 718877 e-mail: mail@netweber.co.uk www.uk.weber

To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.