

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name: weberfloor 4720 epoxy primer - resin

Safety data sheet no.: 44P46063H

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture** Construction chemicals

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:**

Saint-Gobain Weber

Dickens House

Enterprise Way

Flitwick

Bedfordshire MK45 5BY

Tel.: 01525 718877

webersds@saint-gobain.com

**1.4 Emergency telephone number:**

UK: NHS 111 (Members of the public)

UK NPIS 24-hour telephone helpline: +44 (0)344 892 0111 (Healthcare professionals only)

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**



GHS07 GHS09

**Signal word** Warning

**Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 1)

H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P391 Collect spillage.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH205 Contains epoxy constituents. May produce an allergic reaction.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

**Description:** Mixture of substances listed below with non hazardous additions.

**Dangerous components:**

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	25-50%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40-xxxx	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane Alternative CAS number: 9003-36-5 ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	25-50%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-xxxx	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	5-10%

**Additional information** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

Trade name: weberfloor 4720 epoxy primer - resin

(Contd. of page 2)

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

#### After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse liquid should be tempered (20-30°C).

#### After swallowing

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

### 5.2 Special hazards arising from the substance or mixture

 Carbon monoxide (CO)

### 5.3 Advice for firefighters

**Protective equipment:** Wear fully protective suit.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

Trade name: weberfloor 4720 epoxy primer - resin

(Contd. of page 3)

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:** No special measures required.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage**

**Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

Prevent any seepage into the ground.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:**

Store receptacle in a well ventilated area.

Keep container tightly sealed.

None.

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

**8.1 Control parameters**

**Additional information about design of technical facilities:** No further data; see section 7.

**Ingredients with limit values that require monitoring at the workplace:**

DNELs		
<b>CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane</b>		
Oral	Derived No Effect Level	0.5 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	0.75 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	0.0893 mg/kgxday (consumer systemic long term value)
		4.93 mg/m <sup>3</sup> (worker systemic long term value)
		0.87 mg/m <sup>3</sup> (consumer systemic long term value)
<b>Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane</b>		
Oral	Derived No Effect Level	6.25 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	104.15 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	6.25 mg/kgxday (consumer systemic long term value)
		29.39 mg/m <sup>3</sup> (worker systemic long term value)
		8.7 mg/m <sup>3</sup> (consumer systemic long term value)
<b>CAS: 100-51-6 Benzyl alcohol</b>		
Oral	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
Dermal	Derived No Effect Level	8 mg/kgxday (worker systemic long term value)
Inhalative	Derived No Effect Level	4 mg/kgxday (consumer systemic long term value)
		22 mg/m <sup>3</sup> (worker systemic long term value)
		5.4 mg/m <sup>3</sup> (consumer systemic long term value)

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 4)

**PNECs**

**CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane**

Predicted No-Effect Concentration	0.0006 mg/l (sea water rating factor)
	0.006 mg/l (fresh water rating factor)

**8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

**Respiratory protection:**

Use suitable respiratory protective device only when aerosol or mist is formed.

Filter A2/P2.

**Protection of hands:** Protective gloves.

**Material of gloves**

Nitrile rubber, NBR

Butyl rubber, BR

**Penetration time of glove material**

The determined breakthrough times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the breakthrough time, is recommended.

Thickness $\geq$ 0.4mm.

**Eye protection:** Goggles recommended during refilling

**Body protection:** Protective work clothing.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Light yellow
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not applicable.

**Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	201 °C (DIN)

**Flash point:** 101 °C (DIN ISO 2592)

**Flammability (solid, gas):** Not applicable.

**Auto-ignition temperature:** 184 °C (DIN 51794)

**Decomposition temperature:** Not determined.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 5)

<b>Ignition temperature:</b>	Product is not self-igniting.
<b>Explosive properties:</b>	Product does not present an explosion hazard.
<b>Explosion limits:</b>	
<b>Lower:</b>	1.3 Vol % (DIN 51649)
<b>Upper:</b>	13.0 Vol % (DIN 51649)
<b>Oxidising properties</b>	Not determined.
<b>Vapour pressure at 20 °C:</b>	0.1 hPa (DIN 51640)
<b>Density:</b>	Not determined
<b>Bulk density:</b>	Not applicable.
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix
<b>Segregation coefficient (n-octanol/water) log Pow:</b>	Not determined.
<b>Viscosity:</b>	
<b>dynamic:</b>	Not determined.
<b>kinematic:</b>	Not determined.
<b>Solvent separation test:</b>	Not determined
<b>Solvent content:</b>	
<b>Organic solvents:</b>	9.8 %
<b>EU-VOC (%)</b>	9.7744 %
<b>EU-VOC (g/L)</b>	97.7440 g/l
<b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

**10.2 Chemical stability** Stable at recommended storage conditions

**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions**

May produce violent reactions with bases and numerous organic substances including alcohols and amines

Exothermic polymerisation.

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 6)

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

Components	Type	Value	Species
<b>CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane</b>			
Oral	LD50	>15,000 mg/kg	(Rat)
Dermal	LD50	>23,000 mg/kg	(Rat)
<b>Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane</b>			
Oral	LD50	>5,000 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rat)
<b>CAS: 100-51-6 Benzyl alcohol</b>			
Oral	LD50	1,620 mg/kg	(Rat)
Dermal	LD50	>2,000 mg/kg	(Rabbit)
Inhalative	LC50/4 h	>4.178 mg/l	(Rat)

**Primary irritant effect:**

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**Additional toxicological information:**

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:** No further relevant information available.

Type of test	Effective concentration	Method	Assessment
<b>CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane</b>			
IC50/72h	1.7-1.8 mg/l	(Fish)	
LC50/48h	2.7 mg/l	(Daphnia magna)	
	1.85-2.7 mg/l	(Fish)	
LC50/96h	1.2-3.6 mg/l	(Fish)	
EC50/24h	4.6 mg/l	(Daphnia magna)	

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 7)

EC50/48h	1.1-2.8 mg/l (Daphnia magna) 9.1 mg/l (Algae)
EC50/72h	9.4-11 mg/l (Algae)
NOEC (72h)	2.4-4.2 mg/l (Algae)
NOEC (21d)	0.3 mg/l (Daphnia magna)
<b>Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane</b>	
LC50/48h	2.55 mg/l (Fish)
EC50/48h	1.6-3.5 mg/l (Daphnia magna)
EC50/72h	1.8 mg/l (Algae)
NOEC (21d)	0.3 mg/l (Daphnia magna)
<b>CAS: 100-51-6 Benzyl alcohol</b>	
LC50/48h	260 mg/l (Daphnia magna) 645 mg/l (Leuciscus idus (Orfe))
LC50/96h	10 mg/l (Lepomis macrochirus (Sunfish)) 460 mg/l (Pimephales promelas (Minnow))
EC50/24h	400 mg/l (Daphnia magna)
EC50/48h	230 mg/l (Daphnia magna)
EC50/96h	400 mg/l (Daphnia magna) 640 mg/l (Scenedesmus subspicatus (Algae))
EC50/72h	770 mg/l (Algae)
NOEC (72h)	310 mg/l (Algae)
NOEC (21d)	51-66 mg/l (Daphnia magna)
EC 10	400 mg/l (Pseudomonas putida (Bacteria))

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential**

**CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane**

EBAB 3.242 log Pow

**Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane**

EBAB 3.6 log Pow (Bioaccumulation)

**CAS: 100-51-6 Benzyl alcohol**

EBAB 1.05 log Pow (Bioaccumulation)

**12.4 Mobility in soil** No further relevant information available.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 8)

**Ecotoxicological effects:**

**Behaviour in sewage processing plants:**

Type of test / Effective concentration / Method / Assessment	
<b>CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane</b>	
EC 50 (3h)	100 mg/l (microorganisms)
<b>Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane</b>	
EC 50 (3h)	100 mg/l (Activated sludge)
<b>CAS: 100-51-6 Benzyl alcohol</b>	
EC 50 (3h)	79 mg/l (Scenedesmus quadricauda (Algae))

**Additional ecological information:**

**General notes:** Danger to drinking water if even small quantities leak into the ground.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Does not contain PBT substances.

**vPvB:** Does not contain vPvB substances.

**12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Uncleaned packaging:**

**Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

**SECTION 14: Transport information**

<b>14.1 UN-Number</b> ADR, IMDG, IATA	UN3082
<b>14.2 UN proper shipping name</b> ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
<b>IMDG</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin, Epoxy Resin), MARINE POLLUTANT
<b>IATA</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11


Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 9)

**14.3 Transport hazard class(es)**

**ADR, IMDG, IATA**



**Class** 9 Miscellaneous dangerous substances and articles.  
**Label** 9

**14.4 Packing group**

**ADR, IMDG, IATA** III

**14.5 Environmental hazards:**

Product contains environmentally hazardous substances: Epoxy Resin, Epoxy resin

**Marine pollutant:**

Yes  
Symbol (fish and tree)

**Special marking (ADR):**

Symbol (fish and tree)

**Special marking (IATA):**

Symbol (fish and tree)

**14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

**EMS Number:**

F-A,S-F

**Stowage Category**

A

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

**Transport/Additional information:**

Not dangerous according to the above specifications.

**ADR**

**Limited quantities (LQ)**

5L

**Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**Transport category**

3

**Tunnel restriction code**

(-)

**Remarks:**

Exemptions Special provision 375

**IMDG**

**Limited quantities (LQ)**

5L

**Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**Remarks:**

Exemptions Special provision 969

**IATA**

**Remarks:**

Exemptions Special provision 197

**UN "Model Regulation":**

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 9, III

GB

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 10)

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poisons Act**

**Regulated explosives precursors**

None of the ingredients is listed.

**Regulated poisons**

None of the ingredients is listed.

**Reportable explosives precursors**

None of the ingredients is listed.

**Reportable poisons**

None of the ingredients is listed.

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category E2** Hazardous to the Aquatic Environment

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

**Department issuing SDS:** EHS

**Contact:**

webersds

01525718877

webersds@saint-gobain.com

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 12)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 06.02.2024

Version number 11

Revision: 06.02.2024

**Trade name: weberfloor 4720 epoxy primer - resin**

(Contd. of page 11)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

GB