

Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: weberfloor 4720 epoxy primer - hardener

Safety data sheet no.: 44P46064F

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber

Dickens House

**Enterprise Way** 

Flitwick

Bedfordshire MK45 5BY

Tel.: 01525 718877

webersds@saint-gobain.com

1.4 Emergency telephone number:

UK: NHS 111 (Members of the public)

UK NPIS 24-hour telephone helpline: +44 (0)344 892 0111 (Healthcare professionals only)

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

#### **Hazard pictograms**





GHS05 GHS07

Signal word Danger



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

(Contd. of page 1)

#### **Hazard statements**

H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P260 Do not breathe dusts or mists.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### 2.3 Other hazards

# Results of PBT and vPvB assessment PBT: Does not contain PBT substances. vPvB: Does not contain vPvB substances.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture consisting of the following components.

| Dangerous components:   |   |        |
|---|---|--------|
| CAS: 2855-13-2<br>EINECS: 220-666-8<br>Index number: 612-067-00-9<br>Reg.nr.: 01-2119514687-32-xxxx | 3-aminomethyl-3,5,5-trimethylcyclohexylamine  Skin Corr. 1B, H314; Eye Dam. 1, H318; ♣ Acute Tox. 4, H302; Skin Sens. 1A, H317  Specific concentration limit: Skin Sens. 1A; H317: C ≥  0.001 % | 25-50% |
| CAS: 25513-64-8<br>EINECS: 247-063-2<br>Reg.nr.: 01-2119560598-25-xxxx                              | trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412  | 25-50% |

Additional information For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

#### General information

Never administer anything by mouth to an unconscious person.

If unconscious, place the patient in a stable side position and consult a doctor

Immediately remove any clothing soiled by the product.

After inhalation Supply fresh air; consult doctor in case of complaints.

#### After skin contact

Wash off immediately with plenty of water, continue washing. Seek immediate medical advice.

#### After eye contact

Rinse immediately and abundantly with water. Seek medical attention, if pain or redness persists.

Remove contact lenses, if possible. Continue rinsing

(Contd. on page 3)



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

(Contd. of page 2)

Seek immediate medical advice.

Remove contact lenses after the first 5 minutes and coninue washing.

#### After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Do not give anything by mouth unless the person is fully conscious.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

#### 5.3 Advice for firefighters

#### Protective equipment:

Mouth respiratory protective device.

Wear fully protective suit.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

The product must not get into watercourses or into the soil.

Keep contaminated washing water and dispose of appropriately.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

#### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

#### Information about fire - and explosion protection:

Protect against electrostatic charges.

Protect from heat.

Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

(Contd. of page 3)

## 7.2 Conditions for safe storage, including any incompatibilities Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: None.

7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Additional information about design of technical facilities: No further data; see section 7. Ingredients with limit values that require monitoring at the workplace:

| DNELs  |                         |  |  |  |
|--|-------------------------|--|--|--|
| CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine              |                         |  |  |  |
| Oral   | Derived No Effect Level | 0.3 mg/kgxday (consumer systemic long term value)  |  |  |
|  |                         | 0.3 mg/kgxday (consumer systemic short term value) |  |  |
| Inhalative   | Derived No Effect Level | 0.073 mg/m³ (worker local short term value)        |  |  |
|  |                         | 0.073 mg/m³ (worker local long term value)         |  |  |
| PNECs  |                         |  |  |  |
| CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine              |                         |  |  |  |
| Predicted No-Effect Concentration 0.06 mg/l (fresh water rating factor)  |                         |  |  |  |
| CAS: 25513-64-8 trimethylhexane-1,6-diamine                              |                         |  |  |  |
| Predicted No-Effect Concentration 0.00295 mg/l (sea water rating factor) |                         |  |  |  |
|  |                         | 0.0295 mg/l (fresh water rating factor)            |  |  |

#### 8.2 Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

#### Respiratory protection:

Use suitable respiratory protection where aerosols/vapours are generated.

Use respiratory equipment with suitable filter or wear self-contined breathing apparatus. (CE approved air-purifying respirator: organic vapour cartirdge with a particulate pre-filter, type AP2).

Protection of hands: Protective gloves.

#### **Material of gloves**

**PVC** gloves

Butyl rubber, BR

Chlorinated polyethylene.

Polethylene.

Ethyl vinyl alcohol laminate (EVAL).

Neoprene.

Nilrile rubber.

(Contd. on page 5)



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

(Contd. of page 4)

#### Penetration time of glove material

The determined breakthrough times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the breakthrough time, is recommended.

Thickness >0.5mm

#### Eye protection:

Use close fitting goggles (EN 166).

Eye wash fountain should be located in immediate work area.

#### **Body protection:**

Use protective clothing chemically resistant to this mateiral.

Remove immediately all contaminated clothing.

## **SECTION 9: Physical and chemical properties**

| 9.1 Information on basic physical and cher<br>General Information | mical properties                              |
|---|---|
| Appearance:   |   |
| Form:   | Fluid   |
| Colour:   | Yellowish                                     |
| Odour:  | Amine-like                                    |
| Odour threshold:  | Not determined.                               |
| pH-value:   | Not applicable.                               |
| Change in condition   |   |
| Melting point/freezing point:                                     | Undetermined.                                 |
| Initial boiling point and boiling range:                          | 232 °C (DIN)                                  |
| Flash point:  | 110 °C (DIN ISO 2592)                         |
| Flammability (solid, gas):  | Not applicable.                               |
| Auto-ignition temperature:  | 350 °C (DIN 51794)                            |
| Decomposition temperature:  | Not determined.                               |
| Ignition temperature:   | Product is not self-igniting.                 |
| Explosive properties:   | Product does not present an explosion hazard. |
| Explosion limits:   |   |
| Lower:  | Not determined.                               |
| Upper:  | Not determined.                               |
| Oxidising properties  | Not determined.                               |
| Vapour pressure:  | Not determined.                               |
| Density:  | Not determined                                |
| Bulk density:   | Not applicable.                               |
| Relative density  | Not determined.                               |
| Vapour density  | Not determined.                               |
| Evaporation rate  | Not determined.                               |
|   | (Contd. on page 6)                            |

(Contd. on page 6)



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

|   | (Contd. of pa                              | ge 5 |
|---|--|------|
| Solubility in / Miscibility with Water: | Not miscible or difficult to mix           |      |
| Segregation coefficient (n-octanol/     | water) log                                 |      |
| Pow:                                    | Not determined.                            |      |
| Viscosity:                              |  |      |
| dynamic:                                | Not determined.                            |      |
| kinematic:                              | Not determined.                            |      |
| Solvent separation test:                | Not determined                             |      |
| Solvent content:                        |  |      |
| Organic solvents:                       | 0.0 %                                      |      |
| 9.2 Other information                   | No further relevant information available. |      |

## **SECTION 10: Stability and reactivity**

**10.1 Reactivity** No further relevant information available.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with oxidizing agents

Reacts with acids

- 10.4 Conditions to avoid Keep away from sources of ignition. Protect from frost.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Ammonia

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

**Acute toxicity** 

Harmful if swallowed or in contact with skin.

LD/LC50 values relevant for classification:

| Compo   | nents   | 1            | Type    | 1 | Value | 1 | Species |  |
|---------|---|--------------|---------|---|-------|---|---------|--|
| CAS: 28 | CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine |              |         |   |       |   |         |  |
| Oral    | LD50  | 1,030 mg/kg  | (ATE)   |   |       |   |         |  |
|         |   | 1,030 mg/kg  | (Rat)   |   |       |   |         |  |
| Dermal  | LD50  | >2,000 mg/kg | g (Rat) |   |       |   |         |  |
| CAS: 2  | CAS: 25513-64-8 trimethylhexane-1,6-diamine                 |              |         |   |       |   |         |  |
| Oral    | LD50  | 910 mg/kg (F | Rat)    |   |       |   |         |  |

#### **Primary irritant effect:**

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

(Contd. on page 7)



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

(Contd. of page 6)

#### Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

| Type of test / Effective concentration / Method / Assessment |   |  |  |  |  |
|--|---|--|--|--|--|
| CAS: 2855-1  | CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine |  |  |  |  |
| LC50/48h   | n 388 mg/l (Daphnia magna)                                  |  |  |  |  |
| LC50/96h   | LC50/96h 110 mg/l (Brachydanio rerio (zebra danio))         |  |  |  |  |
| EC50/24h   | EC50/24h 27 mg/l (Daphnia magna)                            |  |  |  |  |
| EC50/48h   | 23 mg/l (Daphnia magna)                                     |  |  |  |  |
| EC50/72h   | 72h 50 mg/l (Scenedesmus subspicatus (Algae))               |  |  |  |  |
| NOEC (21d)   | 1d) 3 mg/l (Daphnia magna)                                  |  |  |  |  |
| EC 10/18h  | EC 10/18h 11.2 mg/l (Algae)                                 |  |  |  |  |
| CAS: 25513-  | CAS: 25513-64-8 trimethylhexane-1,6-diamine                 |  |  |  |  |
| LC50/48h   | 174 mg/l (Leuciscus idus (Orfe))                            |  |  |  |  |
| EC50/24h   | 31.5 mg/l (Daphnia magna)                                   |  |  |  |  |
| EC50/72h   | 29.5 mg/l (Algae)   |  |  |  |  |

#### **12.2 Persistence and degradability** No further relevant information available.

#### 12.3 Bioaccumulative potential

CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EBAB 0.99 log Pow

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

**PBT:** Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

CB.



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

(Contd. of page 7)

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

| 14.1 UN-Number<br>ADR, IMDG, IATA   | UN2735  |
|---|---|
| 14.2 UN proper shipping name ADR  | 2735 AMINES, LIQUID, CORROSIVE, N.O<br>(TRIMETHYLHEXAMETHYLENEDIAMINE<br>ISOPHORONEDIAMINE) |
| IMDG, IATA  | AMINES, LIQUID, CORROSIVE, N.O (TRIMETHYLHEXAMETHYLENEDIAMINE ISOPHORONEDIAMINE)            |
| 14.3 Transport hazard class(es)   |   |
| ADR   |   |
| S ST  |   |
| Class<br>Label  | 8 (C7) Corrosive substances.<br>8   |
| IMDG, IATA  |   |
| Class<br>Label  | 8 Corrosive substances.   |
| 14.4 Packing group<br>ADR, IMDG, IATA   | III   |
| 14.5 Environmental hazards:   | Not applicable.   |
| 14.6 Special precautions for user<br>Hazard identification number (Kemler code):<br>EMS Number:<br>Segregation groups | Warning: Corrosive substances.<br>80<br>F-A,S-B<br>(SGG18) Alkalis                          |
| Stowage Category Segregation Code   | A SG35 Stow "separated from" SGG1-acids   |

(Contd. on page 9)



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

| 14.7 Transport in bulk according to Annual Marpol and the IBC Code | ex II of Not applicable.  |
|--|---|
| Transport/Additional information:                                  | Not dangerous according to the above specifications.  |
| ADR Limited quantities (LQ) Excepted quantities (EQ)               | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 m |
| Transport category Tunnel restriction code                         | 3<br>E  |
| IMDG Limited quantities (LQ) Excepted quantities (EQ)              | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 m |
| UN "Model Regulation":   | UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S<br>(TRIMETHYLHEXAMETHYLENEDIAMINES<br>ISOPHORONEDIAMINE), 8, III             |

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Poisons Act** 

| Regulated | explosives | precursors |
|-----------|------------|------------|
|           |            |            |

None of the ingredients is listed.

#### Regulated poisons

None of the ingredients is listed.

#### Reportable explosives precursors

None of the ingredients is listed.

#### Reportable poisons

None of the ingredients is listed.

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

(Contd. on page 10)



Printing date 06.02.2024 Version number 11 Revision: 05.02.2024

Trade name: weberfloor 4720 epoxy primer - hardener

(Contd. of page 9)

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

**Department issuing SDS: EHS** 

Contact: webersds 01525718877

webersds@saint-gobain.com

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

GB