

DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014

No: DoP-CE-weberend PTC-020424

1.	Unique identification code of the product-type:				
	weberend PTC				

2. Intended use/es:

Coloured rendering mortar (CR) for external use

3. Manufacturer:

Saint-Gobain Construction Products UK Limited trading as Saint-Gobain Weber Dickens House Enterprise Way Flitwick Beds MK45 5BY UK

Web: www.uk.weber

4. Authorised Representative

Saint-Gobain Construction Products (Ireland) Limited trading as Gyproc Ireland Unit 4, Kilcarbery Business Park
Nangor Road
Dublin 22
Republic of Ireland

Email: weberCE.enquiries@saint-gobain.com

5. System/s of AVCP:

System 4

6. Harmonised standard:

EN 998-1:2016

7. Notified body/ies:

Not applicable

8. Declared performance/s:

EN 998-1





Essential characteristics	Performance	Standard	
Capillary water absorption		BS EN 1015-18:2002 (EN 998-1:2016)	
Water vapour permeability	µ ≤30	BS EN 1015-19:1999 (EN 998-1:2016)	
Thermal conductivity	0.82 W/(m.K)	EN 1745:2012, Table A.12 (EN 998-1:2016)	
Reaction to fire	Class A2-s1,d0	BS EN 13501-1 :2018 (BS EN 998-1:2016, 5.3.3)	
Durability:		EN 998-1:2016, 5.3.2	
Adhesion after weathering cycles	≥0.2 MPa Failure mode A & B	BS EN 1015-21:2002 (EN 998-1:2016)	
Water permeability after weathering cycles	≤1 ml/cm2 after 48 hours		
Dangerous substances	See SDS	EN 998-1:2016, 5.3.4	

NPD = No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[name]	LEE LAMBLE	/	
At [place]	FLITWICK.	On [date of issue]	11/04/24
[signature]	/ bully		

