

DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom

No: DoP-UKCA-weberpral E-250124

1. Unique identification code of the product-type:

weberpral E

2. Intended use/es:

One coat rendering mortar for external use (OC)

3. Manufacturer:

Saint-Gobain Construction Products UK Limited trading as Saint-Gobain Weber
Dickens House
Enterprise Way
Flitwick
Beds
MK45 5BY
UK

Web: www.uk.weber

4. System/s of AVCP:

System 4

5. Designated standard:

EN 998-1:2016

6. Approved body/ies:

Not applicable

7. Declared performance/s:

EN 998-1

Essential characteristics	Performance	Standard
Capillary water absorption	Wc2 class $C \leq 0.2 \text{ kg}/(\text{m}^2 \cdot \text{min}^{0.5})$	BS EN 1015-18:2002 (EN 998-1:2016)
Water vapour permeability	$\mu \leq 15$	BS EN 1015-19:1999 (EN 998-1:2016)
Thermal conductivity	0.61 W/(m.K)	EN 1745:2012, Table A.12 (EN 998-1:2016)
Reaction to fire	Class A1 (<1% organic content)	BS EN 998-1:2016, 5.3.3
Durability:		EN 998-1:2016, 5.3.2
Adhesion after weathering cycles	$\geq 0.2 \text{ MPa}$ Failure mode A & B	BS EN 1015-21:2002 (EN 998-1:2016)
Water permeability after weathering cycles	$\leq 1 \text{ ml}/\text{cm}^2$ after 48 hours	
Dangerous substances	See SDS	EN 998-1:2016, 5.3.4

NPD = No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

[name]

LEE LAMBLET

At [place]

FLITWICK

On [date of issue]

25/01/24

[signature]

[Handwritten signature]